

provisionally

CONSTRUCTION	Tufted 1/12" Loop
STRUCTURE	Tufté 1/12" Bouclé
STRUKTUR	Getuftet 1/12" Schlinge
STRUCTUUR	Getuft 1/12" Luspool

PILE MATERIAL	100% ECONYL® yarn
COUCHE D'USURE	100% Regenerated Solution Dyed Nylon
POLMATERIAL	
POOLMATERIAAL	

SECONDARY BACKING DOSSIER RÜCKENAUSSTATTUNG RUG	comfortBack ^{eco} : shock absorbing and noise reducing carpet tile backing, enhanced with a fully recyclable polyolefin based layer made from minimum 60% post-industrial recycled content
--	---

TOTAL WEIGHT Ca. 3.900 g/m²
POIDS TOTAL
GESAMTGEWICHT
TOTAAL GEWICHT

PILE WEIGHT Ca. 880 g/m²
POIDS DU VELOURS
POLEINSATZGEWICHT
POOLGEWICHT

PILE ABOVE BACKING Ca. 590 g/m²
POIDS DE VELOURS UTILE
POLNUTZSCHICHTGEWICHT
NUTTIG POOLGEWICHT

TOTAL HEIGHT Ca. 9,7 mm
EPAISSEUR TOTALE
GESAMTDICKE
TOTALE DIKTE

PILE HEIGHT Ca. 4,3 mm
EPAISSEUR DU VELOURS
POLDICKE
POOL HOOGTE

PILE DENSITY Ca. 0,137g/cm³
DENSITÉ DU VELOURS
POLROHDICHTHE
POOLDICHTHEID

TUFT DENSITY Ca. 225.000 /m²
NOMBRE DE TOUFFES
NOPPENZAHL
AANTAL PUNTEN

CLASSIFICATION	EN 1307
CLASSEMENT	33- LC2
KLASSIFIKATION	
CLASSIFICATIE	

CASTOR CHAIR SUITABILITY EN 985
EMPLOI CHAISE À ROULETTES A : continuous use
STUHLROLLENEIGNUNG
ROLSTOELGESCHIKTHEID

DONNÉES ENVIRONNEMENTALES

CRADLE TO CRADLE CERTIFIED™	Gold level	130, 352
	Silver level	Other colours

FIRE RESISTANCE EN 13501-1
COMPORTEMENT AU FEU B_{s1}
BRENNVERHALTEN
BRANDGEDRAG

FASTNESS TO LIGHT ISO 105-B02
SOLIDITÉ À LA LUMIÈRE ≥ 7
LICHTTECHTHEIT
LICHTTECHTHEID

RUBBING FASTNESS EN ISO 105-X12
SOLIDITÉ AU FROTTMENT ≥ 4
REIBECHTHEIT
WRIJFECHTHEID

COLOUR FASTNESS TO WATER EN ISO 105-E01
SOLIDITÉ À L'EAU ≥ 4
WASSERRECHTHEIT
WATERECHTHEID

THERMAL RESISTANCE ISO 8302
RÉSISTANCE THERMIQUE 0,13 m²K/W
WÄRMEDURCHLABWIDERSTAND
WARMTEDOORLAATWEERSTAND

IMPACT NOISE RATING ISO 10140
ISOLATION PHONIQUE ΔL_w : 30 dB
TRITTSCHALVERBESSERUNGSGRADE
GELUIDSABSORPTIE

SOUND ABSORPTION ISO 354
ABSORPTION PHONIQUE
SHALLABSORPTIONSGRAD
GELUIDSABSORPTIE α_w : 0,30

PERMANENT ANTISTATIC ISO 6356
ANTISTATIQUE PERMANENT
PERMANENT ANTISTISCH
PERMANENT ANTISTATISCH
≤ 2 kV

TRANSVERSAL RESISTANCE	ISO/DIS 10965
RESISTANCE TRANSVERSALE	$\leq 10^{11}$ Ohm
DURCHGANGSWIDERSTAND	
DOORGANGSWEERSTAND	

SIZE & PACKING	50 cm x 50 cm
DIMENSION & EMBALLAGE	box: 4m ²
ABMESSUNG & VERPACKUNG	pallet: 20 boxes
Afmeting & verpakking	


NUMBER OF COLOURS 10
NOMBRE DE COLORES
ANZAHL DER FARBEN
AANTAL KLEUREN

DIMENSIONAL STABILITY	EN 986
STABILITE DIMENSIONNELLE	max. 0,2 %
DIMENSIONSTABILITÄT	
DIMENSIONELE STABILITEIT	

GUT-NR FE552ACA

LEED® Product contributes toward satisfying Credits under LEED®.*

DGNB modulyss is member of DGNB, the German Sustainable Building Council



modulyss
Zevensterrestraat 21
B 9240 Zele
T +32 (0)52 80 80 80
F +32 (0)52 80 82 00
info@modulyss.com
www.modulyss.com

We reserve all rights for technical improvements | Technische wijzigingen, ter verbetering van het product, worden voorbehouden | Sous réserve de toute modification technique visant à l'amélioration constante de nos produits

Durch technische Weiterentwicklung sind bedingte Änderungen vorbehalten

* For more information, visit the modules sustainable databases, i.e. Remark. Products are not reviewed under LEED®. LEED® credit requirements cover the performance of materials in aggregate, and the performance of individual products of brands. The LEED® green building certification program is the national accepted benchmark for the design, construction, and operation of green buildings. For more information on LEED®, visit www.usgbc.org/contact.