

GLUEDOWN LVT - ALL ABOUT WOOD

French Oak, Vintage Oak



Construction	High Performance Luxury Vinyl Tile
Finish	ProGuard MAX™ UV-Cured Urethane
Wear Layer Thickness	0.55 mm
Overall Thickness	2.5 mm
Edge Profile	Micro Bevel with Matte Bevel Technology™
Product Weight	4000 g/m²

PERFORMANCE

Flammability/Smoke Emissions (EN 13501-1)	Class Bfl-s1
Use Classification (EN ISO 10874)	Class 33 Heavy Commercial, Class 42 General Light Industrial
Dimensional Stability (EN ISO 23999)	Requirement - ≤0.25 %, Curl ≤2 mm. Typical results - ≤0.10 %, Curl ≤0.5 mm
Residual Indentation (EN ISO 24343-1)	≤0.1 mm
Colour Fastness to Light (EN ISO 105-B02)	≥6
Castor Chair Resistance (Type W) (EN ISO 4918)	Pass
Chemical Resistance (EN ISO 26987)	Excellent
Electrostatic Propensity (EN ISO 1815)	≤2.0 kV
Slip Resistance (EN16165 Annex B / DIN 51130 - Ramp)	R10
Slip Resistance (EN16165 Annex C / BS 7976 - Pendulum)	≥61 dry; ≥39 wet (low slip potential ≥36)

INSTALLATION

Full spread of permanent adhesive

ENVIRONMENTAL

Minimum of 20% recycled content by total product weight
(Pre Consumer internal waste)

Manufactured in ISO14001 certified location

M/PACT Carbon Neutral Floors,
10.39 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A4)
Cradle to Gate footprint 100% off set

Orthophthalate and REACH SVHC free- compliant to WELL feature
requirement for Enhanced Material Restrictions

Single polymer construction for ease of end-of-life recycling

TILE/PLANK SIZE

200 x 1000mm












BOX QUANTITY

20 pieces / 4.0m²



WARRANTIES

15 year wear warranty

CERTIFICATIONS

	 		 							
--	--	---	--	---	--	---	---	---	--	--

INSTALLATION

 Ashlar Random	 Herringbone
--	--

CE

 DOP 1004-06 BS EN 651	 Bfl-s1	 E1 HCHO	 DS	 DS		
---	---	--	---	---	--	--