

GLASSHOUSE

Eden

Milliken™

| | |
|-------------------------|--|
| Construction | Tufted, Textured Loop Pile |
| Face Fibre | Thrive® matter 90% recycled Nylon |
| Stain Resist | Inherently stain resistant fibre |
| Finished Face Weight | 545 g/m ² |
| Gauge | 47.2 / 10 cm |
| Rows | 41.2 / 10 cm |
| Tuft Density | 194,646 /m ² |
| Finished Pile Height | 3.0 mm |
| Standard Backing | WellBAC® Comfort 90% recycled open cell polyurethane cushion backing. Available with TractionBack® on request |
| Nominal Total Thickness | 9.0 mm |
| Tile Size | 50 cm x 50 cm |
| Nominal Total Weight | 4100g/m ² |
| Tiles per Box | 22 (5.5m ²) |

PERFORMANCE

| | |
|--|---|
| Flammability (Euroclassification EN13501:1-2018) | Class Bfl - s1 |
| Flammability (Radiant Panel ASTM-E-648) | Class 1 |
| Flammability (Hot Metal Nut BS4790) | Low Radius of Char |
| Use Classification (EN 1307) | Class 33 Heavy Commercial Use |
| Castor Chair (BS EN 985:2001) | Class A - Intensive use (r value ≥ 2.4) |
| Static Electricity (ISO 6356) | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3) | 30 dB ΔL _w |
| Sound Absorption (ISO354) | 0.30 Class D |
| Alpha p values | 125Hz 0.00, 250Hz 0.05, 500Hz 0.35, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.40 |

ENVIRONMENTAL

69% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT™ Carbon Offset Floors,
4.55 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3)
Cradle to Gate footprint 100% off set

WARRANTIES

15 year wear warranty


Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

| | | | | | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

INSTALLATION



CE

| | | | | | | | |
|--|--|--|--|--|--|--|--|
| | | | | | | | |
|--|--|--|--|--|--|--|--|