

SISAL EDIT RETOLD

Looma / Meela / Zagora

Milliken™

| | |
|-------------------------|--|
| Construction | Tufted Loop Pile |
| Face Fibre | ECONYL® 100% recycled Nylon |
| Stain Resistance | StainSmart® for stain resist and soil release |
| Finished Face Weight | 410 g/m ² |
| Gauge | 39.4 / 10 cm |
| Rows | 65 / 10 cm |
| Tuft Density | 255,906 /m ² |
| Finished Pile Height | 3.4 mm |
| Standard Backing | WellBAC® Comfort 95% recycled open cell polyurethane cushion backing. Available with TractionBack® on request |
| Nominal Total Thickness | 8.6 mm |
| Tile Size | 50 cm x 50 cm |
| Nominal Total Weight | 3800 g/m ² |
| Tiles per Box | 22 (5.5m ²) |

PERFORMANCE

| | |
|--|---|
| Flammability (Euroclassification EN13501:1-2018) | Class Bfl - s1 |
| Flammability (Radiant Panel ASTM-E-648) | Class 1 |
| Flammability (Hot Metal Nut BS4790) | Low Radius of Char |
| Use Classification (EN 1307) | Class 33 Heavy Commercial Use |
| Castor Chair (BS EN 985:2001) | Class A - Intensive use (r value ≥ 2.4) |
| Static Electricity (ISO 6356) | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3) | 32 dB ΔL_w |
| Sound Absorption (ISO354) | 0.30 Class D |
| Alpha p values | 125Hz 0.05, 250Hz 0.05, 500Hz 0.30, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.35 |

ENVIRONMENTAL

70% recycled content by total product weight

Manufactured in location certified to: ISO9001:2015 / ISO14001 / ISO45001 / ISO50001 using renewable electricity

M/PACT™ Carbon Offset Floors, 4.51 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3) Cradle to Gate footprint 100% off set

WARRANTIES

15 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

| | | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | | | |
| | | | | | | | | | | | |

INSTALLATION



Monolithic

CE



DOP-2895-1004-02
BS EN 14041

