

# WIREFRAME

Wireframe / Wireframe Expressions

Construction	Tufted, Level Loop Pile
Face Fibre	100% Nylon
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	420 g/m <sup>2</sup>
Gauge	39.4 / 10 cm
Rows	68 / 10 cm
Tuft Density	267,720 /m <sup>2</sup>
Finished Pile Height	3.4 mm
Standard Backing	Comfort Lite 90% recycled open cell polyurethane cushion backing Available with TractionBack® on request
Nominal Total Thickness	8.6 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	3700 g/m <sup>2</sup>
Tiles per Box	20 (5m <sup>2</sup> )

## PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	32 dB
Sound Absorption (ISO354)	0.30 Class D
Alpha s values	125Hz 0.02, 250Hz 0.04, 500Hz 0.38, 1000Hz 0.23, 2000Hz 0.28, 4000Hz 0.37

## ENVIRONMENTAL

60% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

EPD, TUV certified

## WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

## CERTIFICATIONS


## INSTALLATION



Monolithique

## CE MARKING

18  
DOP-0338-100402  
EN 14041:2004